

NAME

combine - combine images to create new images.

SYNOPSIS

combine [*options ...*] *image composite* [*mask*] *combined*

DESCRIPTION

combine combine images to create new images.

EXAMPLES

To combine a image of a cockatoo with a perch, use

```
combine cockatoo.miff perch.ras composite.miff
```

To compute the difference between images in a series, use

```
combine -compose difference series.1 series.2 difference.miff
```

To combine a image of a cockatoo with a perch starting at location (100,150), use

```
combine -geometry +100+150 cockatoo.miff perch.ras composite.miff
```

To tile a logo across your image of a cockatoo, use

```
convert +shade 30x60 cockatoo.miff mask.miff
combine -compose bumpmap -tile logo.gif cockatoo.miff mask.miff composite.miff
```

OPTIONS

-blend *value*

blend the two images a given percent.

-colors *value*

preferred number of colors in the image.

The actual number of colors in the image may be less than your request, but never more. Note, this is a color reduction option. Images with less unique colors than specified with this option will have any duplicate or unused colors removed. Refer to **quantize(9)** for more details.

Note, options **-dither**, **-colorspace**, and **-treedepth** affect the color reduction algorithm.

-colorspace *value*

the type of colorspace: **GRAY**, **OHTA**, **RGB**, **Transparent**, **XYZ**, **YCbCr**, **YIQ**, **YPbPr**, **YUV**, or **CMYK**.

Color reduction, by default, takes place in the RGB color space. Empirical evidence suggests that distances in color spaces such as YUV or YIQ correspond to perceptual color differences more closely than do distances in RGB space. These color spaces may give better results when color reducing an image. Refer to **quantize(9)** for more details.

The **Transparent** color space behaves uniquely in that it preserves the matte channel of the image if it exists.

The **-colors** or **-monochrome** option is required for this option to take effect.

-comment *string*

annotate an image with a comment.

By default, each image is commented with its file name. Use this option to assign a specific

comment to the image. Optionally you can include the image filename, type, width, height, or scene number by embedding special format characters. Embed **%f** for filename, **%d** for directory, **%e** for filename extension, **%t** for top of filename, **%m** for magick, **%w** for width, **%h** for height, **%s** for scene number, **%b** for file size, or **\n** for newline. For example,

```
-comment "%m:%f %wx%h"
```

produces an image comment of **MIFF:bird.miff 512x480** for an image titled **bird.miff** and whose width is 512 and height is 480.

If the first character of *string* is **@**, the image comment is read from a file titled by the remaining characters in the string.

-compose *operator*

the type of image composition.

By default, each of the composite image pixels are replaced by the cooresponding image tile pixel. You can choose an alternate composite operation:

```
over
in
out
atop
xor
plus
minus
add
subtract
difference
bumpmap
replace
```

How each operator behaves is described below.

- over** The result will be the union of the two image shapes, with *composite image* obscuring *image* in the region of overlap.
- in** The result is simply *composite image* cut by the shape of *image*. None of the image data of *image* will be in the result.
- out** The resulting image is *composite image* with the shape of *image* cut out.
- atop** The result is the same shape as image *image*, with *composite image* obscuring *image* where the image shapes overlap. Note this differs from **over** because the portion of *composite image* outside *image*'s shape does not appear in the result.
- xor** The result is the image data from both *composite image* and *image* that is outside the overlap region. The overlap region will be blank.
- plus** The result is just the sum of the image data. Output values are cropped to 255 (no overflow). This operation is independent of the matte channels.
- minus** The result of *composite image* - *image*, with underflow cropped to zero. The matte channel is ignored (set to 255, full coverage).
- add** The result of *composite image* + *image*, with overflow wrapping around (*mod* 256).
- subtract** The result of *composite image* - *image*, with underflow wrapping around (*mod* 256). The **add** and

subtract operators can be used to perform reversible transformations.

difference

The result of `abs(composite image - image)`. This is useful for comparing two very similar images.

bumpmap

The result *image* shaded by *composite image*.

replace The resulting image is *image* replaced with *composite image*. Here the matte information is ignored.

The image compositor requires a matte, or alpha channel in the image for some operations. This extra channel usually defines a mask which represents a sort of a cookie-cutter for the image. This is the case when matte is 255 (full coverage) for pixels inside the shape, zero outside, and between zero and 255 on the boundary. For certain operations, if *image* does not have a matte channel, it is initialized with 0 for any pixel matching in color to pixel location (0,0), otherwise 255 (to work properly **borderwidth** must be 0).

-compress *type*

the type of image compression: *None*, *JPEG*, *LZW*, *RunlengthEncoded*, or *Zip*.

Specify **+compress** to store the binary image in an uncompressed format. The default is the compression type of the specified image file.

-density *<width>x<height>*

vertical and horizontal resolution in pixels of the image.

This option specifies an image density when decoding a Postscript or Portable Document page. The default is 72 pixels per inch in the horizontal and vertical direction.

-displace *<horizontal scale>x<vertical scale>*

shift image pixels as defined by a displacement map.

With this option, *composite image* is used as a displacement map. Black, within the displacement map, is a maximum positive displacement. White is a maximum negative displacement and middle gray is neutral. The displacement is scaled to determine the pixel shift. By default, the displacement applies in both the horizontal and vertical directions. However, if you specify *mask*, *composite image* is the horizontal X displacement and *mask* the vertical Y displacement.

-display *host:display[.screen]*

specifies the X server to contact; see **X(1)**.

-dispose *method*

GIF disposal method.

Here are the valid methods:

- 0 No disposal specified.
- 1 Do not dispose.
- 2 Restore to background color.
- 3 Restore to previous.

-dither apply Floyd/Steinberg error diffusion to the image.

The basic strategy of dithering is to trade intensity resolution for spatial resolution by averaging the intensities of several neighboring pixels. Images which suffer from severe contouring when reducing colors can be improved with this option.

The **-colors** option is required for dithering to take effect.

-font *name*

This option specifies the font to be used for displaying normal text. The default is **fixed**.

-geometry *<width>{<percent>x<height>{<percent>{<+-><x offset>{<+-><y offset>{<!>{<>{<>}}*

the width and height of the image.

By default, the width and height are maximum values. That is, the image is expanded or contracted to fit the width and height value while maintaining the aspect ratio of the image. Append an exclamation point to the geometry to force the image size to exactly the size you specify. For example, if you specify **640x480!** the image width is set to 640 pixels and height to 480. If only one factor is specified, both the width and height assume the value.

To specify a percentage width or height instead, append **%**. The image size is multiplied by the width and height percentages to obtain the final image dimensions. To increase the size of an image, use a value greater than 100 (e.g. 125%). To decrease an image's size, use a percentage less than 100.

Use **>** to change the dimensions of the image *only* if its size exceeds the geometry specification. **>** resizes the image *only* if its dimensions is less than the geometry specification. For example, if you specify **640x480>** and the image size is 512x512, the image size does not change. However, if the image is 1024x1024, it is resized to 640x480.

By default the images are combined relative to the image gravity (see **-gravity**). Use *<x offset>* and *<y offset>* to specify a particular location to combine the images.

-gravity *direction*

direction image gravitates to within the composite. See **X(1)** for details about the gravity specification.

The image may not fill the composite completely (see **-geometry**). The direction you choose specifies where to position the image within the composite. For example *Center* gravity forces the image to be centered within the composite. A gravity of *Forget* stretches the composite to the same size as the image. By default, the image gravity is *NorthWest*.

-interlace *type*

the type of interlacing scheme: **None**, **Line**, **Plane**, or **Partition**. The default is **None**.

This option is used to specify the type of interlacing scheme for raw image formats such as **RGB** or **YUV**. **No** means do not interlace (RGBRGBRGBRGBRGB...), **Line** uses scanline interlacing (RRR...GGG...BBB...RRR...GGG...BBB...), and **Plane** uses plane interlacing (RRRRRR...GGGGGG...BBBBBB...). **Partition** is like plane except the different planes are saved to individual files (e.g. image.R, image.G, and image.B).

Use **Line**, or **Plane** to create an interlaced GIF or progressive JPEG image.

-label *name*

assign a label to an image.

Use this option to assign a specific label to the image. Optionally you can include the image filename, type, width, height, or scene number in the label by embedding special format characters. Embed **%f** for filename, **%d** for directory, **%e** for filename extension, **%t** for top of filename, **%m** for magick, **%w** for width, **%h** for height, **%s** for scene number, **%b** for file size in kilobytes, or **\n** for newline. For example,

-label "%m:%f %wx%h"

produces an image label of **MIFF:bird.miff 512x480** for an image titled **bird.miff** and whose width is 512 and height is 480.

If the first character of *string* is @, the image label is read from a file titled by the remaining characters in the string.

When converting to Postscript, use this option to specify a header string to print above the image.

-matte store matte channel if the image has one.

-monochrome

transform the image to black and white.

-negate apply color inversion to image.

The red, green, and blue intensities of an image are negated. Use **+negate** to only negate the grayscale pixels of the image.

-page <width>{%}x<height>{%}{+-}<x offset>{+-}<y offset>{!}{<}{>}

preferred size and location of an image canvas.

Use this option to specify the dimensions of the Postscript page in dots per inch or a TEXT page in pixels. The choices for a Postscript page are:

Letter	612x 792
Tabloid	792x1224
Ledger	1224x 792
Legal	612x1008
Statement	396x 612
Executive	540x 720
A3	842x1190
A4	595x 842
A5	420x 595
B4	729x1032
B5	516x 729
Folio	612x 936
Quarto	610x 780
10x14	720x1008

For convenience you can specify the page size by media (e.g. A4, Ledger, etc.). Otherwise, **-page** behaves much like **-geometry** (e.g. -page letter+43+43>).

To position a GIF image, use -page +LEFT+TOP (e.g. -page +100+200).

The default page dimensions for a TEXT image is 612x792.

-quality *value*

JPEG quality setting.

Quality is 0 (worst) to 100 (best). The default is 75.

-scene *value*

image scene number.

-size <width>{%}x<height>{%}{+offset}{!}

width and height of the image.

Use this option to specify the width and height of raw images whose dimensions are unknown such as **GRAY**, **RGB**, or **CMYK**. In addition to width and height, use **-size** to skip any header information in the image or tell the number of colors in a **MAP** image file, (e.g. **-size 640x512+256**).

-stereo combine two image to create a stereo anaglyph.

The left side of the stereo pair is saved as the red channel of the output image. The right side is saved as the green channel. Red-blue stereo glasses are required to properly view the stereo image.

-tile repeat composite operation across image.

-treedepth *value*

Normally, this integer value is zero or one. A zero or one tells **combine** to choose a optimal tree depth for the color reduction algorithm.

An optimal depth generally allows the best representation of the source image with the fastest computational speed and the least amount of memory. However, the default depth is inappropriate for some images. To assure the best representation, try values between 2 and 8 for this parameter. Refer to **quantize(9)** for more details.

The **-colors** option is required for this option to take effect.

-verbose

print detailed information about the image.

This information is printed: image scene number; image name; combined image name; image size; the image class (*DirectClass* or *PseudoClass*); the total number of unique colors; and the number of seconds to read and combine the image.

Options are processed in command line order. Any option you specify on the command line remains in effect until it is explicitly changed by specifying the option again with a different effect.

Change '-' to '+' in any option above to reverse its effect. For example, specify **+matte** to store the image without its matte channel.

By default, the image format is determined by its magic number. To specify a particular image format, precede the filename with an image format name and a colon (i.e. **ps:image**) or specify the image type as the filename suffix (i.e. **image.ps**). See **convert(1)** for a list of valid image formats.

When you specify **X** as your image type, the filename has special meaning. It specifies an X window by id, name, or **root**. If no filename is specified, the window is selected by clicking the mouse in the desired window.

Specify *image* as - for standard input, *combined* as - for standard output. If *image* has the extension **.Z** or **.gz**, the file is uncompressed with **uncompress** or **gunzip** respectively. If *combined* has the extension **.Z** or **.gz**, the file size is compressed using with **compress** or **gzip** respectively. Finally, precede the image file name with / to pipe to or from a system command.

Use an optional index enclosed in brackets after a file name to specify a desired subimage of a multi-resolution image format like Photo CD (e.g. **img0001.pcd[4]**) or a range for MPEG images (e.g. **video.mpg[50-75]**). A subimage specification can be disjoint (e.g. **image.tiff[2,7,4]**). For raw images, specify a subimage with a geometry (e.g. **-size 640x512 image.rgb[320x256+50+50]**).

The optional **mask** can be used to provide matte information for **composite** when it has none or if you want

a different mask. A mask image is typically grayscale and the same size as **composite**. If the image is not grayscale, it is converted to grayscale and the resulting intensities are used as matte information.

If *combined* already exists, you will be prompted as to whether it should be overwritten.

ENVIRONMENT

display To get the default host, display number, and screen.

SEE ALSO

display(1), animate(1), import(1), montage(1), mogrify(1), convert(1), xtp(1)

COPYRIGHT

Copyright 1997 E. I. du Pont de Nemours and Company

Permission to use, copy, modify, distribute, and sell this software and its documentation for any purpose is hereby granted without fee, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of E. I. du Pont de Nemours and Company not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. E. I. du Pont de Nemours and Company makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

E. I. du Pont de Nemours and Company disclaims all warranties with regard to this software, including all implied warranties of merchantability and fitness, in no event shall E. I. du Pont de Nemours and Company be liable for any special, indirect or consequential damages or any damages whatsoever resulting from loss of use, data or profits, whether in an action of contract, negligence or other tortious action, arising out of or in connection with the use or performance of this software.

AUTHORS

John Cristy, E.I. du Pont De Nemours and Company Incorporated